

180mm Aerfoam Insulated Duct 90° Bend



Centrotherm
solutions beyond

Article number: 188283





Product overview

The Aerfoam 180 mm 90° bend allows directional changes within the Aerfoam system. Made of expanded polyethylene (EPE) duct, it minimises the risk of condensation and energy loss. It is very light and extremely easy and safe to install. All Aerfoam parts connect to each other using strong, airtight mechanical connections. They can also be securely mounted to walls or ceilings using brackets. Aerfoam is ideal for both central mechanical ventilation and domestic hot water heat pump systems.

- Insulated to minimise the risk of condensation and energy loss.
- Easy mechanical connection and mounting.
- Lightweight and easy to cut, ensuring quick installation.
- Impact resistant.

Product dimensions



180mm Aerfoam Insulated Duct 90° Bend



Centrotherm
solutions beyond

Article number: 188283

Technical specifications

Technical	
Color	Gray
Insulated	☒
Diameter inner	180 mm
Diameter outer	212 mm
Insulation thickness	16 mm
Performance	
Insulation performance	0.041 W/m.K
Temperature resistance (min.)	-30 °C
Temperature resistance (max.)	60 °C
Installation temperature (min.)	-30 °C
Installation temperature (max.)	60 °C
Zeta supply 1 connection	0.84
Zeta extract 1 connection	0.84
Dimensions	
Length gross	298 mm
Width	212 mm
Height	298 mm
Net weight	0.09 kg

© 2026 Ubbink. All rights reserved. | Content is subject to change without notice. Availability and configurations may differ per country. | UB-25-06-2026-INT-EN

180mm Aerfoam Insulated Duct 90° Bend



Centrotherm
solutions beyond

Article number: 188283

Technical details

DN180 90° Elbow		
Zeta [-]	0,84	
Qv [m³/h]	Δp [Pa]	V [m/s]
50	0,15	0,55
100	0,6	1,09
150	1,35	1,64
200	2,4	2,18
250	3,75	2,73
300	5,41	3,27
350	7,36	3,82
400	9,61	4,37
450	12,16	4,91
500	15,01	5,46
550	18,17	6
600	21,62	6,55
650	25,37	7,1
700	29,43	7,64