

# 180mm Aerfoam Insulated Duct 2m



Centrotherm  
solutions beyond

Article number: 188206




## Product introduction

The Aerfoam 180 mm Duct is made of expanded polyethylene (EPE), which minimises the risk of condensation and energy loss. It is very light and extremely easy and safe to install. All Aerfoam parts connect to each other using strong, airtight mechanical connections. They can also be securely mounted to walls or ceilings using brackets. Aerfoam is ideal for both central mechanical ventilation and domestic hot water heat pump systems.

- Insulated to minimise the risk of condensation and energy loss.
- Easy mechanical connection and mounting.
- Lightweight and easy to cut, ensuring quick installation.
- Impact resistant.

## Product dimensions



# 180mm Aerfoam Insulated Duct 2m



Centrotherm  
solutions beyond

Article number: 188206

## Technical specifications

Specifications	
Technical	
Color	Gray
Insulated	<input checked="" type="checkbox"/>
Diameter inner	180 mm
Diameter outer	212 mm
Insulation thickness	16 mm
Performance	
Insulation performance	0.041 W/m.K
Temperature resistance (min.)	-30 °C
Temperature resistance (max.)	60 °C
Zeta supply 1 connection	0.12
Zeta extract 1 connection	0.12
Dimensions	
Length gross	2000 mm
Width	212 mm
Height	212 mm
Net weight	0.54 kg

© 2026 Ubbink. All rights reserved. | Content is subject to change without notice. Availability and configurations may differ per country. | UB-03-02-2026-INT-EN

# 180mm Aerfoam Insulated Duct 2m



Centrotherm  
solutions beyond

Article number: 188206

## Technical details

Aerfoam duct		
Diameter	180	
Qv [m <sup>3</sup> /h]	v [m/s]	$\Delta p$ [Pa]
100	1,1	1,0
200	2,2	1,0
300	3,3	1,0
400	4,4	1,6
500	5,5	2,5
600	6,5	3,6